

UR10

Technical details

Specification

Payload	10 kg /22 lbs
Reach	1300 mm / 51.2 in
Degrees of freedom	6 rotating joints
Programming	Polyscope graphical user interface on 12 inch touchscreen with mounting

Performance

Repeatability	±0.1 mm / ±0.0039 in (4 mils)
Ambient temperature range	0-50°C
Power consumption	Min 90W, Typical 250W, Max 500W
Collaboration operation	15 advanced adjustable safety functions. TüV NORD Approved Safety Function Tested in accordance with: EN ISO 13849:2008 PL d

Movement

Axis movement robot arm	Working range	Maximum speed
Base	± 360°	± 120°/Sec.
Shoulder	± 360°	± 120°/Sec.
Elbow	± 360°	± 180°/Sec.
Wrist 1	± 360°	± 180°/Sec.
Wrist 2	± 360°	± 180°/Sec.
Wrist 3	± 360°	± 180°/Sec.
Typical tool	1 m/Sec. / 39.4 in/Sec.	

Features

IP classification	IP54	
ISO Class Cleanroom	5	
Noise	72dB(A)	
Robot mounting	Any	
Estimated life at rated loads	35,000 hours	
I/O ports	Digital in	2
	Digital out	2
	Analog in	2
	Analog out	0
I/O power supply in tool	12 V/24 V 600 mA in tool	

Physical

Footprint	Ø 190mm
Materials	Aluminium, PP plastics
Tool connector type	M8
Cable length robot arm	6 m / 236 in
Weight with cable	28,9 kg / 63.7 lbs

Control Box

Features

IP classification	IP20	
ISO Class Cleanroom	6	
Ambient temperature range	0-50°C	
I/O ports	Digital in	16
	Digital out	16
	Analog in	2
	Analog out	2
I/O power supply	24V 2A	
Communication	TCP/IP 100Mbit, Modbus TCP, Profinet, EthernetIP	
Power source	100-240 VAC, 50-60 Hz	

Physical

Control box size (WxHxD)	475 x 423 x 268 mm
	18.7 x 16.7 x 10.6 in
Weight	15 kg / 33.1 lbs
Materials	Steel

Teach Pendant

Features

IP classification	IP20
--------------------------	------

Physical

Materials	Aluminium, PP
Weight	1,5 kg / 3.3 lbs
Cable length	4,5 m / 177 in

